




FÜR HANDWERK, DAS ÜBERZEUGT.

TECHNICAL DATA SHEET

BLANKE AQUA-GLASS

An innovative and user-friendly profile for walls with integrated appliance for partition walls of glass in addition to BLANKE AQUA-KEIL GLASS



Technical Data

Length:	2,0 m
Height:	25,0 mm
Length:	2,1 m
Height:	25,0
Possible size of the tile:	until 12,0 mm
Possible size of the glass:	until 12,0 mm
Depth of the appliance for the glass:	13,0 mm
Profil strength:	0,8 mm
Setting leg:	31,5 mm
Material:	stainless steel V2A brushed stainless steel V2A satin stainless steel chrome plated (1.4301)

Characteristics

- > Vertically appliance for partition walls of glass
- > Assembly without drilling at the shower area
- > Installation without cutting tiles
- > Easy to install inside of the gaps

Description

Blanke AQUA-GLASS is a profile for walls of stainless steel for the appliance for partition walls of glass. At once the profile can be used as an optical access from shower areas to contiguously areas between tiles and plaster. Moreover, the profile can be installed easily inside of the gaps. Blanke AQUA-GLASS is available in left and right versions.

Application area

Blanke AQUA-GLASS is usable for the appliance for partition walls of glass in shower areas with bathrooms and showers in private and public areas.

Working instructions

Press in the perforated setting leg of BLANKE AQUA-GLASS into the fresh adhesive bed and bring it into the correct position. The mounting height of BLANKE AQUA-KEIL GLASS has to be taken into account. If the profile has to be cutted out please use a metal bracket saw. Observe that the tiles have to be layed next to the profile without any hollows. There should be a gap next to the profile of 2 mm. The setting leg of the profile uses the joint space so that no cutting of the tile is needed. After grouting the tiles the profile has to be closed to both sides with a natural cross-linked silicone.

For cleaning the stainless steel do not use any steel wool or steel brush. Thereby extraneous rust could occur. Any cleaning agents must not contain hydrochloric acid or chlorine. The partition wall of glass can be insert into the appliance for the profile and has to be sealed.

Attention: There must not be any contact between the glass and the stainless steel. Therefore, please use able spacer. The gap between the glass and the appliance for the profile has to be filled in with silicone.

Attention: When applying our products, please note that our current technical data sheets have to be followed. Valid rules and standards have to be complied with as well.

Blanke Systems GmbH & Co. KG

Stenglingser Weg 68-70
58642 Iserlohn/Germany

T +49 (0)2374 507-0
F +49 (0)2374 507-4230

E info@blanke-systems.de
I www.blanke-systems.de

Verfasser: AWT 02.05.2013