



FÜR HANDWERK, DAS ÜBERZEUGT.

## TECHNICAL DATA SHEET

# BLANKE BALCONY-EDGE PROTECTOR PRO

Balcony tile end profile



### Characteristics

- > Colour stability
- > Weather and UV resistant
- > Protects the exposed edges
- > Suitable for gutters

### Description

The BLANKE BALCONY-EDGE PROTECTOR PRO is a balcony profile for the exposed tile edge. It protects the exposed edges from weather and decay and ensures a clean edge. It also offers the simple and uncomplicated integration of a gutter system (BLANKE RINSYS). The system is completed by a wide range of connectors for inner and outer corners.

### Technical Data

|                    |             |
|--------------------|-------------|
| Length supplied :  | 2,5 m       |
| Layer thickness:   | 10,5 mm     |
| Covering height:   | 55.1 mm     |
| Profile thickness: | 1.5 mm      |
| Support bar:       | 88.7 mm     |
| Material:          | Aluminium   |
| Colour             | middle grey |

|   |         |
|---|---------|
| BLANKE BALCONY- EDGE PROTECTOR connector: |         |
| Height:                                   | 10.5 mm |
| Width:                                    | 40.0 mm |

|   |                    |
|---|--------------------|
| BLANKE BALCONY- EDGE PROTECTOR profile<br>outside corner 90°: |                    |
| Height:   | 10.5 mm            |
| Outer dimension:  | 240 x 240 x 955 mm |

|                            |                   |
|----------------------------|-------------------|
| BLANKEUNIVERSAL-connector: |                   |
| Height:                    | 0.8 mm            |
| Material:                  | Metal; galvanized |

### Application area

The BLANKE BALCONY-EDGE PROTECTOR PRO is used in the system without drainage with the BLANKE DIBA sealing on balconies and terraces.

### Working instructions

The BLANKE BALCONY-EDGE PROTECTOR PRO perforated support bar is embedded in the edge of the screed in a contact surface of thin adhesive and completely plastered over. In the front support area of the profile a large spot of BLANKE DIBA-COLL gluing and sealing material must be deposited with which the BLANKE DIBA 20 is glued in. After this glue BLANKE DIBA 100 across the whole surface, starting from the support bar.

Attention: The proper and successful application of our products is outside our control. Therefore, we can only guarantee the quality of our products within the scope of our terms and conditions. However, we cannot be held responsible for the successful application of our product. This data sheet shall render all previous technical information about this product invalid. We reserve the right to changes based on technical advancements. Information that exceed the scope of this bulletin and is provided by our staff, requires our written confirmation.

### Blanke Systems GmbH & Co. KG

Stenglingser Weg 68-70  
58642 Iserlohn/Germany

T +49 (0)2374 507-0  
F +49 (0)2374 507-4230

E info@blanke-systems.de  
I www.blanke-systems.de

Verfasser: AWT 02.05.2013